

**BILZ PRODUCTS - MADE IN GERMANY** 

# PRECISE AND NON-SLIP MACHINE INSTALLATION IN SPECIAL ENVIRONMENTS

We enable technology leaders in industry and research to run their plants vibration free - for safe, fast work processes and precise results.

The new Bilz levelling wedges in stainless steel are machine feet for the finest levelling when installing machines, particularly under high loads.







# SERIES PKA-VA | PKD-VA


Bolt-on (PKA-VA) / bolt-through precision levelling wedge (PKD-VA) in stainless steel, particularly suitable for machines in the food and luxury food industry, packaging, chemical and recycling industry.


### PKA-VA





PKD-VA





# **DESCRIPTION**

- Bilz precision levelling wedge PKA-VA (bolt-on) / PKD-VA (bolt-through) in stainless steel version 1.4301. The levelling wedge is very easy to adjust and particularly suitable for chemical, hygienic and outdoor applications.
- The bolt-on levelling wedges remain in position even when the machine is lifted, significantly easing the installation of the machine.
- All sizes also available with stainless steel spherical seat (PKAK-VA/PKDK-VA).
- Vibration Isolation is possible by adding Bilz insolation pads (also in EPDM or VITON)
- For applications in clean rooms, we provide special solutions without lubricants.
- We are also able to develop a wide range of special solutions.
   We are always happy to offer our advice.
- General tolerances in accordance with ISO 2768 mK.
- Fixing bolts: Suitable bolts and nuts with standard thread can be supplied on request. Delivery includes 1 nut and 1 washer.

## **VARIANTS**



Especially suitable for machines in the food and luxury food industry, packaging, chemical and recycling industries. Easily adjustable, particularly suitable for applications in the chemical, hygiene and outdoor area.

Тур	item no.	max. load N/pc.	L mm	B mm	H center position mm	d mm	e mm	Inter- nal thread	Adjust- ment range
PKA 1-VA	15-0001	20.000	115	115	44	50	24	M16	+3/-3
PKA 2-VA	15-0020	40.000	150	150	47	60	24	M18	+3/-5

Тур	item no.	max. load N/pc.	L	B mm	H center position mm	d mm	e mm	drill hole	Adjust- ment range
PKD 1-VA	15-0010	20.000	115	115	44	50	24	22	+3/-3
PKD 2-VA	15-0030	40.000	150	150	47	60	24	22	+3/-5



Mounting with Bilz insulation pads is also possible (also in EPDM or VITON).